

## Product Data Sheet

### Train-N

#### Product Description

meeting table is a piece of furniture designed for use in conference rooms, boardrooms, and other professional settings where people gather for discussions, presentations, and collaborative work. Here are some key features and benefits of meeting tables:

Elevate your office space with our innovative Meeting table, designed to cater to the needs of the modern professional. This stunning Meeting table combines style, functionality, and convenience, making it the perfect addition to any office environment.

#### Size and Seating Capacity

Meeting tables come in a variety of sizes to accommodate different room dimensions and seating requirements. Its size of the table is typically determined by the number of people it can seat comfortably.

#### Versatile and Adaptable

This Meeting table is designed to suit a wide range of preferences and needs. Its neutral color scheme and minimalist design make it suitable for various office styles, from traditional to modern. Whether you prefer a clean, minimalist look or a more vibrant workspace, this Meeting table can easily adapt to your personal taste.

#### - Dimensions:

Available over all dimension

-W 3600mm - D 1200 mm-H 1050 mm ◦ with power box (w 313 mm -D 100 mm)

-W 3600mm - D 750 mm-H 1050 mm ◦ with power box (w 313 mm -D 100 mm)

-W 2800 - D 750 mm-H 1050 mm ◦ with power box (w 313 mm -D 100 mm)

-W 3600mm - D 750 mm-H 1050 mm

-W 2800mm - D 750 mm-H 1050 mm

-W 3600mm - D 1200 mm-H 1050 mm

- \*Privacy Features\*: Optional front and side dividers for enhanced privacy.

- \*Cable Management\*: Integrated solutions for electrical cable routing.

Structural Cable Duct, steel profile which serves as cable channel

Cross legs in extruded Tubular Steel, powder coat finish.

Legs are connected to the cable duct with a high pressure Formed Cold Roll Steel

Leg positioning are inset by 600mm to ensure seating capacity on all sides of the table

## Materials

- \*Wood\*:

### Option 1

Melamine MDF-E1 According to European standard EN 13986 Density EN 323 780 ± 5% Kg/m<sup>3</sup> or chipboard Tricolored S5 (CARB FASE 2) Density EN 323 700 ± 7% Kg/m<sup>3</sup> According to Italian national standards UNI U41101400, 18 mm thick, with PVC lipping (Medium Density Fiberboard).

All wood used have a quality certificate for low formaldehyde emission according to CATAS laboratories and FSC certificate.

### Option 2

Medium-Density Fiberboard (MDF) - Raw / Melamine:

MDF Thickness tolerances: Here the thickness expresses the total thickness of the raw Chip board and the coatings of both surfaces of the board.

Resistance to scratching: Does not include the pearlescent surface treatment. Color matching and surface texture: A slight deviation of color and / or surface texture according to Rating<sup>4</sup> EN14323 between the test sample and Kastamonu reference sample. TOLERANCES ON NOMINAL DIMENSIONS\*1-THICKNESS COMPARED TO RATED VALUES-THICKNESS  $t$  RELATIVE TO NOMINAL VALUE EN 14323 mm  $t_{max} - t_{min} \leq 0,6$  LENGTH AND WIDTH EN 14323 mm  $\pm 5$  EDGE DAMAGE EN 14323 mm  $\leq 10$  SURFACE DEFECTS EN 14323 mm<sup>2</sup>/m<sup>2</sup> points  $\leq 2$  SURFACE DEFECTS EN 14323 mm/m<sup>2</sup> line  $\leq 20$  RESISTANCE TO SCRATCHING\*2 EN 14323 N  $\geq 1,5$  RESISTANCE TO CRACKING EN 14323 Rating  $\geq 3$  RESISTANCE TO STAINING EN 14323 Rating  $\geq 3$  RESISTANCE TO ABRASION EN 14323 Revolution Pattern Class 1  $< 50$

Plain Class 3A  $\geq 150$  EN 12460-3 mg /m<sup>2</sup>h E1 for  $\leq 3,5$  E2 for  $3,5 < \text{release} \leq 8$

FORMALDEHYDE RELEASE EN 717-1 mg/m<sup>3</sup> air E1 for  $\leq 0,124$  E2 for  $\geq 0,124$

- \* Base\*:

- Main Legs: steel tube 50 mm x 50 mm x 1.5 mm cold-rolled steel According to European standard EN 10204, welded construction.

- Middle Legs: 30 mm x 1.5 mm cold-rolled steel , 50 mm x 50 mm x 1.5 mm cold-rolled steel and 16 mm x 16 mm x 1.5 mm cold-rolled steel all are According to European standard EN 10204, and Steel sheet Thickness 1.25 mm for cover According to European standard EN 10131 , welded construction.

- Horizontal Beams: 30 mm x 30 mm x 1.5 mm cold-rolled steel According to European standard EN 10204, connected with high-quality aluminum die-cast connectors.

#### Coating

- All metal parts are coated with epoxy polyester, hybrid system for indoor applications.

Standards for powder coating according to:

Gloss capacity EN-ISO 2813

Impact test EN-ISO 6272

Bend test EN-ISO 1519

Cross cut test EN-ISO 2409

PSD: EN-ISO-13320

Film thickness EN-ISO 2360

All according to European and world standards

- \*Electrical Components\*:

- Horizontal power tracks made from 1.00 mm cold-rolled steel According to European standard EN 10131.
- Each Person includes an anodized aluminum electrical box (313 mm x 100 mm).

### Customization Electrical Components

Dual sided socket tower

Cut out on table top to have finished metal edge

N°2x (100 Vac - 240 Vac)/ 1.1A max - USB port 5V/2.5A

Cable duct mounted on the underside of table to guide cables underneath the table top, cable skeleton to run cables from the floor.

### Assembly

The Meeting table comes partially unassembled (assembly by mobica team).

### Warranty

This product is covered by a one-year limited warranty against manufacturer defects.

### Certifications

#### ISO 9001:2015

Quality management systems — Requirements

#### ISO 14001:2015



Environmental management systems — Requirements with guidance for use

#### ISO 45001:2018

Occupational health and safety management systems — Requirements with guidance for use

